U.S. Pat. App. Ser. No. 10/524,702 Attorney Docket No. 10191/4158 Reply to Office Action of April 29, 2008

LISTING OF THE CLAIMS:

Without prejudice, this listing of the claims replaces all prior versions and listings of the claims in the present application:

LISTING of the CLAIMS:

1-13. (Canceled).

14. (Previously Presented) A control unit comprising:

a housing;

a processor situated in the housing; and

at least one inertial sensor situated in the housing,

wherein a data transmission between the processor and the at least one inertial sensor is digital, and

wherein the data transmission is configured in such a way that transmitted data has at least one error bit and at least one status bit, the at least one error bit enabling detection and identification of data transmission errors, and the at least one status bit enabling recognition of an operating state of the at least one inertial sensor.

15. (Previously Presented) The control unit according to claim 14, further comprising a serial synchronous interface for providing the data transmission.

16. (Canceled).

- 17. (Previously Presented) The control unit according to claim 14, wherein the data transmission is configured to be bidirectional.
- 18. (Previously Presented) The control unit according to claim 14, wherein the data transmission is configured for triggering a sensor test.
- 19. (Previously Presented) The control unit according to claim 14, wherein the data transmission is configured for triggering a sensor-internal offset regulation of the at least one inertial sensor.

U.S. Pat. App. Ser. No. 10/524,702 Attorney Docket No. 10191/4158 Reply to Office Action of April 29, 2008

20. (Previously Presented) The control unit according to claim 14, wherein four lines are provided for the data transmission, one of the lines being for selecting the at least one inertial

sensor.

21. (Previously Presented) The control unit according to claim 14, wherein the at least one

inertial sensor has a multi-channel design.

22. (Previously Presented) The control unit according to claim 14, wherein the data

transmission is configured for triggering a switch-over from one operating state to another

operating state of the at least one inertial sensor.

23. (Previously Presented) The control unit according to claim 14, wherein the control unit is

part of a restraint system.

24. (Previously Presented) The control unit according to claim 14, wherein the control unit is

part of a vehicle dynamics control system.

25. (Previously Presented) The control unit according to claim 14, wherein the control unit is

part of one of a sensor box and a sensor cluster.

26. (Previously Presented) The control unit according to claim 14, wherein the control unit is

part of a vehicle navigation system.

27. (Canceled).

28. (Previously Presented) The control unit according to claim 14, wherein the status bit

indicates a running sensor test.

29. (Previously Presented) The control unit according to claim 14, wherein the status bit

indicates an offset regulation mode.

30. (Previously Presented) The control unit according to claim 14, wherein the status bit

indicates an initialization phase.

3